



Typical Inspection Data:

Density @ 20 °C	0.865 g/cm ³
Viscosity @ 100 °C	16.0 cSt
Viscosity @ 40 °C	100 cSt
Calcium	0.29%
Phosphorus	0.05%
Colour	Brown
Pour Point	-39 °C

Performance Profile:

Recommended by Comma for certain Ford, Vauxhall, Mazda, Volvo & VAG Group applications and generally where a 75W-90, API GL-4 oil is specified. Suitable for use where the following specifications are called for:

BMW MTF LF-4, Ford WSD-M2C200-C, Ford WSD-M2C200-B, GM 1940768, GM 1940182, GM 1940764, Volvo 97309, Volkswagen G 50, Nissan MT-XZ Sports & Off-Road Vehicles, Fiat 9.55550-MZ1, API GL-4 (75W-85), API GL-4 synthetic (75W-85 & 75W-90)

Typical Inspection Data are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local Cosan contact or visit www.CommaOil.com.

MVMTF Plus 75W-90

Fully Synthetic

Product Features:

- Fully synthetic manual transmission fluid with excellent bearing and gear protection and proven synchroniser performance.
- Good low temperature performance.
- Excellent cleanliness.
- Robust corrosion protection.
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 01-08-2022