



Typical Inspection Data:

Density @ 20°C	0.850 g/cm ³
Viscosity @ 100°C	14.5 cSt
Viscosity @ 40°C	89 cSt
Viscosity Index	170
Viscosity CCS @ -30°C	6000 cP
T.B.N.	10.0 mg KOH/g
Sulphated Ash Mass	1.1%
Zinc	0.12%
Calcium	0.36%
Phosphorus	0.12%
Colour	Brown
Flash Point (Closed Cup)	210°C
Pour Point	-39°C

Syner-G 5W-40

Synthetic Technology

Official Approvals:

Approved under VW standard 502 00 and VW standard 505 00; MB-Approval 229.3

Recommended by Comma for applications requiring:

MB 229.1, MB 226.5; RN0700, RN0710; ACEA A3/B4; API SN/CF

Product Features:

- Synthetic technology,, high performance 5W-40 oil, for petrol and diesel vehicles including those with fuel injected and multivalved engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 01.08.2023